

## hood |





As a manufacturer of state-of-the-art packaging machines Willems Stretch Hooding BV offers an innovative, high quality and efficient solutions for your packaging on pallets.



## Technical specifications:

Pallet dimensions: 1.200 x 800mm (Euro) Loadheight: min. 250mm 1.200 x 1.000mm (Chep) (incl. pallet) max. 3.000mm\*

Load dimensions: 1.300 x 1.100mm Load tolerance: offset max. 5.00mm

Pallet positioning: ±10mm Maximum load: 1.500Kg

Capacity: till 120 pallets per hour\*

Transportheight 500mm-600mm (standard 600mm) Transportspeed: 12mtr./min. Power supply: 3x400V, 50Hz + Earth + "0" Installed power: 9,6 KW

Diameter filmreel: max. 1.000mm

Required floor space: approx. 3.050 x 4.150 x 3.750mm\* (LxWxH)

(\*depending on project specifications)



Willems stretchhood offers full protection against dirt, dust and moisture. A quality stretchhood film also protects your products against scratches and surface damage. Furthermore, the packaging machines deliver watertight hoods, in order to protect the value of your products.









Almost no maintenance required, the lifting and lowering of the stretch unit happens with toothed belts.



We guarantee the best possible protection for your pallets with our high quality stretchhood



Multifunctional touch panel, easy operation by means of visualization of the operation of the stretchhooder.



The Hooder M
stretchhood offers a
cost-effective
solution for a broad
range of pallet
packages





Smaragdweg 20 • 5527 LB • Hapert • The Netherlands T: +31 (0) 497.64 40 55